

ACS 6200 / 7200 **Series Semi-Automatic Band Sealers**

The ACS 6200/7200 series are semiautomatic bag sealing systems designed horizontal and angled sealing applications such as bakery products, hosiery products, paper products, cases, magazines, and more. With five conveyor lengths to choose from, multiple loading stations can be used to achieve the highest production rate possible. The system has been designed to work with manual, semiautomatic, or fully automated loading Optional product compression systems. belts (pictured) are available to compress excess air out of the package prior to sealing.



Band Sealer Specifications:

Heating Section: 5" (6200), 10" (7200) Cooling Section: 5" (6200), 10" (7200) Temperature Range: 77-450 Degrees F Maximum Speed: 600 Inches per minute (6200), 750 Inches Per Minute (7200)

Standard Seal Width: 1/4"

ACS Conveyor

Conveyor Length: 6', 9', 12', and 15' standard

Conveyor Width: 12" standard

Angle adjustment from: 0-60°(optional) Longer and wider conveyor sizes are

available.

Power Required: 120 Volts. Amperage

varies with conveyor length.

Telephone: 416-291-8085 Toll Free: 800-265-1775 Fax: 416-298-4328

Email: info@plexpack.com

www.plexpack.com



Model	Configuration
ACS 6200 / 7200	Standard Sealer
ACS 6210 / 7210	Standard Sealer with Front End Trimmer
ACS 6220 / 7220	Standard Sealer with Emboss Coder
ACS 6230 / 7230	Standard Sealer with Dry Ink Printer
ACS 6250 / 7250	Standard Sealer with Front End Trimmer & Dry Ink Printer
ACS 6260 / 7260	Standard Sealer with Front End Trimmer & Emboss Coder

PLEXPACK Machinery Distributed By: