

DAMARK

SHRINK PACKAGING SYSTEMS

ECONOMY SEALER & TUNNEL COMBO SYSTEM

Maxipak Series

MP-3



These ruggedly built, economically priced shrink packaging systems are available in three different versions to suit your production needs. The Maxipak series uses quality, brand name components and features Damark quality craftsmanship that is synonymous with shrink packaging.

MP-1

This entry level, table top system is designed to operate in low level production settings (speeds of 4-6 packs per minute).

MP-2

This unit is designed to operate in medium level production settings (speeds of 8-10 packs per minute).

MP-3

This unit is designed to offer production speed outputs (10-12 packs per minute).

DAMARK

SHRINK PACKAGING SYSTEMS

ECONOMY SEALER & TUNNEL COMBO SYSTEM

Maxipak Series

Standard Features: L BAR SEALER

Seal Bar Size	
Width	Length
14"	18"

- Low voltage micro-processor impulse sealing system.
- Easy load and adjust film cradle.
- Counter balanced sealing head with automatic air cushion return.
- Unique seal area raise and lower mechanism.
- Welded steel one piece sealing jaw.
- Roller perforator air venting device (MP-2 and MP-3 only).
- Manual seal bar hold down (MP-1 only).
- Adjustable product loading tray.
- Variable speed product takeaway conveyor in the L Bar Sealer (specific to the MP-3).

Features	Model:	MP-1	MP-2	MP-3
Sealer		✓	✓	✓
Magnet			✓	✓
Flat Discharge Section		✓	✓	
Takeaway Conveyor				✓
Floor Stand Console			✓	✓
✓ = Standard Feature				

GENERAL SPECIFICATIONS

- System works with all shrink films.
- Welded schedule 16 steel sheet construction.
- No tools required for changeover.
- MP-2 and MP-3 come standard with casters.

Standard Features: SHRINK TUNNEL

Tunnel Chamber		
Length	Width	Height
24"	16"	9"

- Dual blower motor/heater system.
- 3200 watt heating capacity.
- Top and side heat vents.
- Digital temperature controller.
- Variable speed Teflon mesh belt conveyor.
- Undershrink (MP-2 and MP-3 only).

TECHNICAL SPECIFICATIONS

	MP-1	MP-2
Electrical	220V/1PH/15A	220V/1PH/16A
Film Width	18" maximum	18" maximum
Unit Dimensions	79" L X 30" W X 22" H	79" L X 30" W X 22" H
Shipping Dimensions	86" L X 34" W X 34" H	86" L X 34" W X 34" H
Shipping Weight	400 lbs.	500 lbs.
F.O.B.	Toronto, Canada	Toronto, Canada

	MP-3
Electrical	220V/1PH/16A
Film Width	18" maximum
Unit Dimensions	79" L X 30" W X 52" H
Shipping Dimensions	86" L X 39" W X 62" H
Shipping Weight	500 lbs.
F.O.B.	Toronto, Canada

DAMARK PACKAGING INC.

phone: 416-609-8011
 toll free: 800-265-1775
 fax: 416-298-4328
 info@damarkpackaging.com
 www.damarkpackaging.com

PLEXPACK



DISTRIBUTED BY

West Coast Plastics Equipment, Inc.
 800-392-8569
 www.sealer.net